

Ducone™

AIR CONDITIONING
AND HEATING

Carefree and
reliable comfort.



Air Conditioners / Heat Pumps

High Efficiency



14

SEER

2AC14(B,L)

2HP14(B,L)

Air Conditioners / Heat Pumps

High Efficiency

14 SEER



L Series



B Series

Save Energy, Save Money*

Our air conditioners and heat pumps have a 14 SEER rating** which provides exceptional heating and cooling performance. They are designed to help you use significantly less energy than units installed as recently as five years ago.

Built To Last

Attractive louvered panels protect the coils and are easy to service, while the compressors are designed for reliable and efficient money-saving performance. Our field-proven, adjustable time / temperature defrost control ensures peak performance is maintained during freezing temperatures. Factory-installed, bi-flow liquid line filter driers protect the compressor from contaminants. The corrosion-resistant cabinet is built from strong, heavy-gauge prepainted steel and has drain holes to prevent the collection of standing water.

* Actual cost savings may vary depending on personal lifestyle, system settings, equipment maintenance, local climate, actual construction, installation of equipment and duct system, hours of operation and local utility rates.

Design Features

- 14 SEER or up to 15 SEER and 8.2 HSPF heating efficiency with specific AHRI matched systems
- 1-1/2 – 5 tons nominal capacity
- Quiet, durable compressor is safeguarded by internal pressure relief valves and inherent thermal protection
- Two coil guard protection options available:
 - Louvered panels provide full metal coil guard ("L" models)
 - Naltex® Hail Guard™ protects from fin damage ("B" models)
- High-quality condenser coils use copper tubes with enhanced louvered fins for maximum heat transfer capability
- Equipped with field-proven 30 / 60 / 90 adjustable time / temperature defrost control
- Permanently lubricated condenser fan motor needs no annual maintenance
- Hinged control panel for simple access to internal components
- Angled service valves allow easy access
- Bi-flow liquid line filter drier protects every unit
- Charged for 15 feet of line set
- All models ETL-, ETLC-, and ARI-listed
- 5-year limited warranty on compressor † and 10-year limited warranty on parts ††

Air Conditioner Unit Dimensions

Model Number	Width (Inches)	Depth (Inches)	Height (Inches)
2AC14(B,L)18P	30	30	26
2AC14(B,L)24P	30	30	26
2AC14(B,L)30P	30	30	34
2AC14(B,L)36P	30	30	34
2AC14(B,L)42P	30	30	42
2AC14(B,L)48P	30	30	42
2AC14(B,L)60P	30	30	42

Heat Pump Unit Dimensions

Model Number	Width (Inches)	Depth (Inches)	Height (Inches)
2HP14(B,L)18P	30	30	26
2HP14(B,L)24P	30	30	26
2HP14(B,L)30P	30	30	30
2HP14(B,L)36P	30	30	30
2HP14(B,L)42P	30	30	42
2HP14(B,L)48P	30	30	42
2HP14(B,L)60P	30	30	42

† Equipment with R22 refrigerant will receive a 5-year limited warranty on the compressor even if registered for the 10-year parts warranty.

†† Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty). Warranty must be registered within 60 days to qualify for 10-year coverage. Unregistered equipment defaults to 5-year coverage. See full warranty at www.alliedair.com for terms, conditions and exclusions.

All specifications and illustrations subject to change without notice and without incurring obligations.

