

Duconne™

AIR CONDITIONING
AND HEATING

Carefree and
reliable comfort.



Gas Furnaces

80_{afue}
DPGB Downflow

Gas Furnaces

80^{afue}



Save Energy, Save Money*

Our whisper burners, dynamically balanced blower wheel and insulated heavy-gauge steel cabinet deliver uncommonly quiet and efficient operation.

Built To Last

The DPGB 80 Furnace is equipped with a Crimp-Tite™ aluminized steel heat exchanger with a lifetime limited warranty on the heat exchanger** and a ten-year limited warranty on parts.*** The hot surface ignition system provides reliable, efficient heat when you need it, with no more pilot lights to re-light.

Gas Furnace Unit Dimensions

Model Number	Width (Inches)	Depth (Inches)	Height (Inches)	Heating Input
DPGB050A3B	13-1/2	29-1/2	38-1/4	50,000
DPGB075A3B	13-1/2	29-1/2	38-1/4	75,000
DPGB075A3B	17	29-1/2	38-1/4	75,000
DPGB100A3B	17	29-1/2	38-1/4	100,000
DPGB100A4B	17	29-1/2	38-1/4	100,000
DPGB100A5B	20-1/2	29-1/2	38-1/4	100,000
DPGB125A5B	20-1/2	29-1/2	38-1/4	125,000

* Actual cost savings may vary depending on personal lifestyle, system settings, equipment maintenance, local climate, actual construction, installation of equipment and duct system, hours of operation and local utility rates.

** Lifetime limited heat exchanger warranty applies to registered equipment only (Standard 20 years with no registration). See full warranty at www.alliedair.com for terms, conditions and exclusions.

*** Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty). Warranty must be registered within 60 days to qualify for 10-year coverage. Unregistered equipment defaults to 5-year coverage. See full warranty at www.alliedair.com for terms, conditions and exclusions.

Design Features

- Up to 80% AFUE
- Heating inputs range from 50,000 – 125,000 Btuh
- 1-1/2 to 5-ton cooling capacity
- Lifetime limited warranty on heat exchanger** and 10-year limited warranty on parts***
- Crimp-Tite™ aluminized steel heat exchanger for longer life and safe operation
- Heavy-gauge, insulated cabinet provides strength and quiet comfort
- Dedicated downflow - no field conversion needed
- Top vent connection allows installation in narrow locations
- Vertical venting or optional horizontal with power venter
- Integrated furnace control with LED diagnostics for fast, accurate troubleshooting
- CSA certified for US and Canada
- Electronic air cleaner, humidifier and continuous fan connections
- Time delay off for air conditioner efficiency enhancement
- Three-speed blower motor
- Twinning compatible
- 5 amp fused low voltage circuit protection

All specifications and illustrations subject to change without notice and without incurring obligations.



Our gas efficiency AFUE ratings are certified by the Gas Appliance Manufacturers Association.

Ducane
AIR CONDITIONING
AND HEATING
www.ducanehvac.com
1-800-448-5872